

# DNA™ 120 Bifacial

Solar for Innovators

Residential | Commercial

## Designed & Engineered in Silicon Valley 370W | 365W | 360W

Our DNA Split-cell Series impressively combines advanced technologies to maximize performance. Produce up to 30% more energy with the bi-facial rear side generation. Our patented DNA, Dual Nano Absorber, technology allows for panel to harvest energy from all directions and operate exceptionally in high heat temperatures.



Produce up to 30% more energy with rear-side generation



Advanced split cell technology with 9 ultra-thin busbars allows for less resistance and more photon capture



Ideal solution for applications affected by shading



All-black design for pristine aesthetics  
No excessive silver bussing or ribbons




Robust product design is resilient in extreme weather. Up to 5400 Pa snow load and 6200 Pa wind Load




30 Year Warranty	3X IEC Standards	RETC Top Performer
------------------	------------------	--------------------

### Linear Performance Warranty



3140 De La Cruz Blvd., Ste  
200 Santa Clara, CA 95054  
www.aptosolar.com  
info@aptosolar.com



## Electrical Specifications

	DNA-120-BF26-360W	DNA-120-BF26-365W	DNA-120-BF26-370W
STCrated Output $P_{mpp}$ (W)	360W	365W	370W
Module Efficiency	19.73%	20.01%	20.28%
Open Circuit Voltage $V_{oc}$ (V)	40.6	40.8	41.0
Short Circiut Current $I_{sc}$ (A)	11.24	11.34	11.44
Rated Voltage $V_{mmp}$ (V)	33.8	34.0	34.2
Rated Current $I_{mmp}$ (A)	10.66	10.75	10.84

Standard Test Conditions for front-face of panel: 1000 W/m<sup>2</sup>, 25°C, measurement uncertainty ≤3%

## Temperature Coefficients

Temperature Coefficients $P_{mmp}$	-0.36%
Temperature Coefficients $I_{sc}$	+0.05%/°C
Temperature Coefficients $V_{oc}$	-0.29%/°C
Normal Operating Cell Temperature (NOCT)	44°C

## Test Operating Conditions

Maximum Series Fuse	20A
Maximum System Voltage	1,000 VDC (UL&IEC)
Maximum Load Capacity (Tested to UL 1703)	5400 Pa Snow Load/ 6200 Pa Wind Load
Fire Performance Class	Class C/Type 1

## Packaging Configuration

Number of Modules per Pallet	31
Number of Pallets per 40ft. Container	26
Pallet Dimensions	1800 X 1130 X 1200
Pallet Weight (kg)	689.3
Container Weight (kg)	17923


## Certifications



## Mechanical Properties

Cell Type	Monocrystalline
Glass	3.2mm, anti-reflection coating, high transmission, low iron, tempered glass
Frame	Anodized Aluminum Alloy
Junction Box	IP68
Dimensions	1756 X 1039 X 35mm
Output Cable	4mm <sup>2</sup> (EU)12AWG
Weight	46.9lbs.(21.3kg)
Cable Length	47.24in,1200mm
Encapsulant	POE

## I-V Curve



## Bifacial Output

$P_{mpp}$ (W) at STC	360	355	350
Bi-facial Boost 5%	378	456	367
Bi-facial Boost 10%	396	372	385
Bi-facial Boost 15%	414	408	402