



DNA-108-N-Type Monofacial

440W | 445W | 450W


DNA-108-MFN10-440W

Residential | Commercial

Our DNA Split Cell Series uses advanced N-Type technology with thin film layers to improve heat tolerance, maximize energy harvest, minimize resistive loss, and use 5% more of the available active area for optimal power performance.

Linear Performance Warranty

Industry Leading 30 Years Product and Performance Warranty



Key Features:

Advanced Technology


Patented DNA™ technology boosts power performance & module efficiency.

Miami-Dade Approved

Miami-Dade County wind load certified to withstand up to 5400 Pa.

Bankable Investment

Comprehensive warranty that covers both 30-year product and 30-year power performance.



Designed and Engineered In
Silicon Valley



Aesthetics



All black design with advanced split cell technology features 16 ultra-thin busbars that allow for less resistance and greater energy harvest.

Awards

Winners of the Leadership in Solar Energy award for three consecutive years and listed as one of the Top Solar Products from 2021-2022.

Certifications





Mechanical Properties

Cell Type	N-TYPE Technology
Glass	3.2mm(0.12in), anti-reflection coating, high transmission, low-iron, tempered glass
Frame	Anodized Aluminum Alloy
Junction Box	IP68
Dimensions	67.7 X 44.6 X 1.3 in, 1722 X 1134 X 35 mm
Weight	46.29lbs. (21kg)
Output Cable	4mm ² (EU)12AWG
Cable Length	47.2 in, 1200mm
Encapsulant	POE and EVA
Connector Type	Staubli EVO2

Electrical Specifications

	DNA-108-MFN10-440W		DNA-108-MFN10-445W		DNA-108-MFN10-450W	
	STC	NOCT	STC	NOCT	STC	NOCT
STC Rated Output P_{mpp} (W)	440W	336W	455W	340W	450W	344W
Open Circuit Voltage V_{OC} (V)	39.03	37.48	39.16	37.57	39.29	37.66
Short Circuit Current I_{SC} (A)	13.73	11.20	13.81	11.32	13.89	11.44
Rated Voltage V_{mpp} (V)	33.48	31.92	33.62	31.99	33.76	32.06
Rated Current I_{max} (A)	13.15	31.92	13.25	10.63	13.35	10.73
Module Efficiency	22.53%		22.79		23.04%	

STC for front-face of panel: 1000 W/m², 25°C, measurement uncertainty <3%
NOCT for front-face of panel: 800W/m², 45°C, Wind speed 1 m/s


Packaging Configuration

Number of Modules per Pallet	31
Number of Pallets per 40ft. Container	26
Pallet Dimensions	68.97 X 44.48 X 49.76 in, 1752 X 1130 X 1264 mm
Pallet Weight (lbs)	1380.43
Modules per 40ft. Container	806

Temperature Coefficients

Temperature Coefficients P_{mpp}	-0.29%/°C
Temperature Coefficients I_{SC}	+0.046%/°C
Temperature Coefficients V_{OC}	-0.23%/°C
Nominal Operating Cell Temperature (NOCT)	45°C±2

I-V Curve



Test Operating Conditions

Maximum Series Fuse	25A
Maximum System Voltage	1,500 VDC (UL&IEC)
Maximum Load Capacity (Per UL 1703)	5400 Pa Snow Load / 5400 Pa Wind Load**
Fire Performance Type	Type 1

Ref_06.16.2026